

Gladiator[®]

High Speed Trailer Tires

GLADIATOR ST LIMITED WARRANTY

American Pacific Industries, Inc. (API) hereby warrants that every new Gladiator ST Trailer Tire purchased from API bearing the brand name Gladiator to be free from conditions of workmanship and material that would cause the tire to become unserviceable for the life of the original tread less 2/32". The life of the original usable tread ends when the tire tread has worn to 2/32" remaining as measured in the fastest wearing groove, at which point the tire is considered to be fully worn out. This warranty applies only to the original purchaser for a period of two (2) years from the date of manufacture. API's liability under this warranty shall be limited to replacement and/or credit for the cost of the tire excluding FET.

GENERAL WARRANTY AND WARRANTY OBLIGATION

If any Gladiator ST tire becomes unserviceable, API will do either of the following:

- A. If the tire becomes unserviceable due to material or workmanship during the first 2/32" of the original tread, API will replace such tire with a comparable new Gladiator tire free of charge. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.
- B. If the tire becomes unserviceable due to material or workmanship after the first 2/32" of tread wear, a credit excluding FET will be given toward the purchase of a comparable new tire in proportion to the usable tread remaining as measured in the fastest wearing groove. Applicable taxes on the new tire and costs of mounting and balancing service shall be borne by the owner.

EXCLUSIONS

- A. All API warranties are limited to the original purchaser and the original vehicle on which they are mounted and are not assignable to subsequent purchasers or vehicles.
- B. This limited warranty is only applicable in the United States and Canada and any tire used on a vehicle registered or operated outside of these areas is not covered by this warranty.
- C. The following is not covered by the Limited Warranty:
 1. Tires branded or marked "Non-Adjustable" (N/A) or "Blemished (Blem)", or previously adjusted.
 2. Tires that are deemed out-of-round or out-of-balance
 3. Failure, damage or irregular wear due to:
 - a. Road hazards (i.e. puncture, cut, snag, impact breaks, etc.);
 - b. Fire, accident or vandalism;
 - c. Mechanical condition of vehicle, including improper alignment, improper inflation, wheel imbalance, faulty shocks or brakes;
 - d. Misapplication of the tire, use of improper inner tube;
 - e. Alteration of the tire or addition of foreign material or transfer from one vehicle to another;
 4. Cost of service, mounting and dismounting.
 5. Loss of time or use, inconvenience, or any incidental or consequential damages of any type or nature.

OWNER'S OBLIGATIONS

In order to be eligible for Limited Warranty Service, the owner must:

- A. Present the tire to an authorized dealer;
- B. Present proof of purchase to the satisfaction of the dealer;
- C. Complete and sign an API Warranty Claim Form, which is available from any authorized dealer;
- D. Pay the amount due on a new tire, less the amount of credit, including taxes, mounting and balancing charges or cost of other services ordered.

DISCLAIMER

This warranty, or any warranty stated or referred to herein, is exclusive and in lieu of any other warranty regarding the quality of API tires, whether expressed or implied, and remedies for breach thereof shall be limited to those specifically provided herein.

Gladiator[®]

High Speed Trailer Tires



EXPERIENCE THE DIFFERENCE[®]



"I run Gladiator All Steel's on my 20,000 LB 5th wheel trailer with no issues and excellent tread wear! I also run the QR25's on my 20' flatbed trailer. From wild to mild, I know I can count on my Gladiator Tires to get the job done."

- Blake Wilkey  /WILKEYWORKS  @BLAKEWILKEY357  @SHREDDYLYFE

Blake Wilkey is an X Comp brand ambassador, off road risk taker, and pushes the limits to see what Gladiator Tires are capable of.

QR25-TS

- Trailer tire designed for recreational vehicle and light industrial use
- Advanced tread compound designed to improve fuel economy and resist weather cracking
- Designed with stone ejectors between the tread area to protect casing and prevent stone drilling
- "N" Speed rating to cover the highest legal speed limits

Size	Ply Rating	Load Index (S/D)	Speed Symbol	Tread Depth (32nds)	Outside Diameter (In)	Section Width (In)	Load Capacity (S/D) LBS
ST175/80R13	6	91/87	N	7	24.0	7.0	1360/1200
ST205/75R14	8	105/101	N	7	26.1	7.0	2040/1820
ST215/75R14	6	102/98	N	7	26.7	8.5	1870/1650
ST205/75R15	8	107/102	N	8	27.1	8.0	2150/1870
ST225/75R15	10	117/112	N	8	28.3	9.2	2830/2470
ST225/90R16	14	124/120	N	8	31.8	8.7	3520/3080
ST235/80R16	12	126/122	N	8	30.8	9.3	3740/3300
ST235/85R16	14	129/125	N	8	31.7	9.3	4080/3640
ST235/85R16	14	132/127	N	8	31.7	9.3	4400/3860



GLADIATOR ALL STEEL

- High mileage tire designed for continuous use and rated "N" speed rated to cover the highest legal speed limits
- Ideal for heavy industrial and hauling equipment
- All Steel construction for added strength and stability

Size	Ply Rating	Load Index (S/D)	Speed Symbol	Tread Depth (32nds)	Outside Diameter (In)	Section Width (In)	Load Capacity (S/D) LBS
ST235/80R16	14	128/124	N	10.5	30.8	9.3	3960/3520
ST235/85R16	14	129/125	N	10.5	31.7	9.3	4080/3640
ST235/85R16	14	132/127	N	10.5	31.7	9.3	4400/3860



QR15-STB

- Bias trailer tire construction
- Tough sidewall for increased sidewall puncture resistance and stability
- Advanced tread compound designed to improve fuel economy and resist weather cracking
- Designed with stone ejectors between the tread area to protect casing and prevent stone drilling

Size	Ply Rating	Load Index (S/D)	Speed Symbol	Tread Depth (32nds)	Outside Diameter (In)	Section Width (In)	Load Capacity (S/D) LBS
ST175/80D13	6	91/87	L	8	24.0	7.0	1360/1200
ST205/75D14	6	100/96	L	9	26.1	8.0	1760/1570
8-14.5	14	120	J	8	27.8	8.0	3100
ST205/75D15	6	101/97	L	9	27.1	8.0	1820/1610
ST225/75D15	8	113/108	L	9	28.3	8.8	2540/2200
205/90D15	10	110/105	J	13	29.6	8.0	2335/2040
225/90D16	10	116/112	J	13	31.8	8.5	2755/2470
225/90D16	12	118/114	J	13	31.8	8.5	2910/2605



QUALITY SPEAKS FOR ITSELF®